Wind Turbine Generators with Reduced Reliance on Rare Earth Magnets

Henriksen, Matthew Lee; Jensen, Bogi Bech

Publication date:
2012

Document Version
Publisher's PDF, also known as Version of record

Technical University of Denmark

DTU

DTU Electrical Engineering
Department of Electrical Engineering

Wind Turbine Generators with Reduced Reliance on Rare Earth Magnets

Matthew L Henriksen, Bogi B Jensen

Center for Electric Power and Energy, Technical University of Denmark

Introduction

- Motivation and goal
  - Recent volatile trends in the rare earth supply chain have been observed.
  - Powerful rare earth permanent magnets (REPM) are the key ingredients to many modern, highly-efficient wind turbine generators (WTG).
  - In this three-year project, finding the best wind turbine topology to use in the event that REPM usage becomes impractical is the ultimate goal.
- Strategy
  - Establish the baseline performance of wind turbines employing REPM.
  - Optimize some alternative generators and compare to the baseline results.
  - Pick a winner, and verify the concept through design and construction of a scaled prototype.

Wind turbine drivetrains: to gear, or not to gear?

- Many drivetrain configurations are currently being marketed:
  - High-speed gearing (classic solution)
  - Direct-drive (newer)
  - "Hybrid" drivetrain (newest)



Figure 1 : Generalized trends. Note that little information on reliability of modern commercial wind turbines is available.

- Wind turbine gearboxes can be very reliable, however reducing the number of stages or removing the gearbox may increase the overall system reliability.



(a) Parallel stage



(b) Planetary stage

Figure 2 : Wind turbine gearboxes are composed of one or more planetary or parallel stages.

- A "hidden cost" associated with the direct-drive concept is the need for a robust support structure to maintain the air gap.



Figure 3 : Examples of support structures for a rotor and stator of a direct-drive wind turbine

- Air gap deformation should be limited to 10-20%, which presents a significant challenge.



Figure 4 : Estimated displacement (m) due to attractive force between rotor and stator of a direct-drive wind turbine

Baseline study: synchronous machines with REPM

- Advantages:
  - Torque density
  - High efficiency at partial load
- Disadvantages:
  - Rare earth prices
  - Demagnetization can occur.



Figure 5 : Cross sectional view of a 3MW DDPMSG. Radius at air gap is 2.3m, length is 1.6m, rated torque is 1.9MNm. Plot on left shows flux lines and flux density at no-load.

Synchronous reluctance machines

- Advantages:
  - No magnets
  - Potentially a robust construction
- Disadvantages:
  - Poor power factor
  - Torque ripple may be an issue.



Figure 6 : Cross sectional view of a 3MW SynRM. Radius at air gap is 0.7m, length is 0.8m, rated torque is 28kNm. Plot on left shows flux lines and flux density at full-load.

Synchronous machines with ferrite magnets

- Advantages:
  - Ferrite magnets are low in cost.
  - Flux concentrating arrangements can be used to generate a high flux density in the air gap.
- Disadvantages:
  - Machine is likely to be heavier.
  - May be more sensitive to demagnetization currents



Figure 7 : Ferrite magnets arranged in a spoke manner can produce an air gap flux density higher than their remanent flux density, which is likely to be 0.3-0.4 Tesla.

Future Work

- Consider additional generator concepts:
  - Induction machines
  - Electrically-excited synchronous machines
  - Others?
- Endorsement of best option or options
- Construction and testing of scaled prototype

Acknowledgement

- Thanks to DONG Energy for their contributions in funding and advising of this project.
- Testing of the prototype machine will take place at PowerLabDK.